

DP 640-644

Desiccant Dryers

Flexibility and energy saving

Benefits:

- Versatility of usage.
- High energy efficiency.
- Optimised consumption of cooling water.
- Wide variety of configurations.
- Simplified access to all components.
- Minimum footprint.
- Microprocessor control with multi-language alphanumeric display.
- Precise electronic control of the process temperature with self-tuning PID algorithm.
- Automatic setting of the safety temperature of the process air.
- Warnings for the correct functioning of the coolers.



Wf Winfactory 4.0
4.0 R E A D Y

Double desiccant tower models, provide 1000 m³/h and 1400 m³/h of dried air respectively, production range from 450 to 800 kg/h. The whole drying system works in closed

loop so as to guarantee a process independent from the environmental conditions, with a Dew Point of -50°C or lower.

Customer oriented solutions:

Versatility of usage:

- Can be used in different production processes, to treat also materials with particular characteristics (such as PET and PETG).

High energy efficiency:

- The patented devices for consumption management - IES (Intelligent Energy Supervisor) and IMD (Intelligent Material Drying), self-adjust the drying parameters to the real production conditions of the processing machines. They allow the costs for energy to be kept in a range from 0.05 kWh/kg up to 0.08 kWh/kg max (process temperature ranging from 80 to 120°C).

Optimised consumption of cooling Water:

- To the EMK Kit permits the operator to manage the water flow according to the set temperature.

Wide variety of configurations:

- Available in the MT (max. temperature 150°C), and HT (for a temperature range up to 200°C) versions, PTU multihopper version, specific configuration for PET and PTU multi hopper (maximum capacity: 4500 litres).

Minimum footprint :

- The best ratio performance/dimensions.



991D113 - Disclaimer: data in this document may be out of date. Please consult technical data sheet

TECHNICAL DATA		DP640	DP644
Process airflow *	m ³ /h	1000/1200*	1400/1500*
Regeneration airflow	m ³ /h	220	220
Process blower *	kW	12.5/14.5*	15/17.5*
Heating power (process)	kW	37.8/50.4*	50.4/63*
Regeneration air blower	kW	1.6/2.1*	1.6/2.1*
Heating power (regeneration)	kW	17.1	
Noise level	db	<80	
Average consumption at 80°C	kWh	23	25
Max process temperature	°C	180	
Dew Point	°C	-45	-60
Standard electrical connection	V/-/Hz	400/3/50 380/3/60 460/3/60	
Dimensions (LxWxH)	mm	1485x1440x2370	
Weight	kg	1100	1200

* HT version

SINGLE HOPPER CONFIGURATION					
MODELS	T2000	T2500	T3000	T3500	T4000
DP 640					
DP 644					